

Callies Finish Ground Cam List - Duramax

Callies Part #	Solid or Hyd	Duration @ .050		Advertised Duration (@ .020)		Cam Lift		Valve Lift w/1.36 int 1.69 ex Rocker		LSA + Advance	Lobe Ctr.		Lift @ TDC		Specific Remarks	
		Intake	Exhaust	Intake	Exhaust	Intake	Exhaust	Intake	Exhaust		Intake	Exhaust	Intake	Exhaust		
270 - Duramax																
270-007	SR	185	187	215	224	0.307	0.250	0.418	0.423	106 + 4	102	110	0.024	0.020	Alternate Firing Order - 8620 carburized	
270-006	SR	185	187	215	224	0.307	0.250	0.418	0.423	106 + 4	102	110	0.024	0.020	Standard Firing Order - 8620 carburized	
270-001	SR	185	187	215	224	0.307	0.250	0.418	0.423	108 + 4	104	112	0.024	0.020	Alternate Firing Order - 8620 carburized	
270-009	SR	185	187	215	224	0.307	0.250	0.418	0.423	108 + 4	104	112	0.024	0.020	Same as 270-001 except 4150 Induction hardened	
270-003	SR	185	187	215	224	0.307	0.250	0.418	0.423	108 + 4	104	112	0.024	0.020	Standard Firing Order - 4150 induction hardened	
270-002	SR	185	187	215	219	0.346	0.281	0.471	0.475	110 + 4	106	114	0.022	0.014	Alternate Firing Order - 8620 carburized	
270-008	SR	185	187	215	219	0.346	0.281	0.471	0.475	110 + 4	106	114	0.022	0.014	Same as 270-002 except 4150 Induction hardened	
270-004	SR	186	190	215	223	0.300	0.250	0.408	0.423	106 + 2	104	108	0.026	0.030	Alternate Firing Order - VTG - 4150 induction hardened	
270-005	SR	190	194	219	227	0.300	0.250	0.408	0.423	108 + 2	106	110	0.026	0.030	Alternate Firing Order - VTG - 4150 induction hardened	