MITSUBISHI



Performance Engine Components by Callies

Sport Series Crankshafts by Compstar are all sold balanced and ready for assembly. All SS crankshafts also feature the best metallurgy and heat treatment on the market today.





Average weight 36 lbs

| Stroke: | Main: | Pin: | Part # |
|---------|-------|------|--------|
| 88mm | 57mm | 45mm | S23013 |
| 100mm | 57mm | 45mm | S23015 |

Mitsubishi 4G63 7 Bolt

Average weight 33 lbs

| Stroke: | Main: | Pin: | Part # | |
|---------|-------|------|--------|--------|
| 88mm | 57mm | 45mm | S23002 | Forged |
| 100mm | 57mm | 45mm | S23008 | Forged |
| 88mm | 57mm | 45mm | S23001 | Billet |
| 94mm | 57mm | 45mm | S23003 | Billet |
| 100mm | 57mm | 45mm | S23007 | Billet |
| 102mm | 57mm | 45mm | S23009 | Billet |



Mitsubishi 4B11 Average weight 32 lbs

Standard Features

- 8 counterweight design
- 4340 steel certified by Callies in house Metallurgical lab
- Ultra-Case nitriding performed and certified by Callies
- Rod and main journal surface finish refined to 4Ra or less
- All journals ground with strength enhancing Tru-Form radii
- Limited stroke availability
- · Aeroshed finishing optional

Mitsubishi 4B11 Billet

Average weight 36 lbs

| Stroke: | Main: | Pin: | Part # |
|---------|-------|------|--------|
| 94mm | 52mm | 52mm | S23004 |
| 96mm | 52mm | 52mm | S23005 |
| 98mm | 52mm | 52mm | S23006 |

Mitsubishi 4G63 Billet and Forged

Standard Features

- 8 counterweight design
- 4340 steel certified by Callies in house Metallurgical lab
- Ultra-Case nitriding performed and certified by Callies
- Rod and main journal surface finish refined to 4Ra or less
- All journals ground with strength enhancing Tru-Form radii
- Limited stroke availability
- Aeroshed finishing optional

Mitsubishi 4G63 7 Bolt - Full CWT Average weight 36 lbs

| Stroke: | Main: | Pin: | Part # | |
|---------|-------|------|--------|----------|
| 88mm | 57mm | 45mm | S23017 | Full CWT |
| 94mm | 57mm | 45mm | S23018 | Full CWT |
| 100mm | 57mm | 45mm | S23019 | Full CWT |
| 102mm | 57mm | 45mm | S23020 | Full CWT |



4G63 Ultra Enforcer Connecting Rod I-Beam

| <u>Length</u> | Journal | Pin | Part # | |
|--|---------------|---------------|--------|--|
| 5.906" / 150mm | 1.890" / 45mm | 0.866" / 22mm | U16730 | |
| 6.024" / 153mm | 1.890" / 45mm | 0.866" / 22mm | U16740 | |
| 6.142" / 156mm | 1.890" / 45mm | 0.866" / 22mm | U16750 | |
| ** also available with Custom Age Bolts ** add -CA to part # | | | | |

4B11T Ultra Enforcer Connecting Rod I-Beam

| Length | Journal | Pin | Part # |
|----------------|---------------|---------------|-----------|
| 5.659" / 144mm | 2.165" / 52mm | 0.906" / 23mm | U16720-CA |

Mitsubishi 4G63 SS Connecting Rod H-Beam

| Length | Journal | Pin | Part # |
|----------------|---------------|---------------|-----------|
| 5.906" / 150mm | 1.890" / 45mm | 0.866" / 22mm | C23101 |
| 5.906" / 150mm | 1.890" / 45mm | 0.866" / 22mm | C23101-CA |
| 6.142" / 156mm | 1.890" / 45mm | 0.866" / 22mm | C23103 |
| 6.378" / 162mm | 1.890" / 45mm | 0.866" / 22mm | C23104 |

Mitsubishi 4B11T SS Connecting Rod H-Beam

| Length | Journal | Pin | Part# |
|----------------|---------------|---------------|-----------|
| 5.659" / 144mm | 2.165" / 52mm | 0.906" / 23mm | C23102 |
| 5.659" / 144mm | 2.165" / 52mm | 0.906" / 23mm | C23102-CA |